			MATERI	AL SAI	FETY	DATA	SHEET	SECTION			
ALDON	ALDON CORPO	RATION	221 Rochester Street Avon, New York 144 (585) 226-6177		MSDS No. Effective D		60 iry 1, 2007	Threshold L Effects of O			
SECTIC	DN I	NAM	=	24 HOUF	REMERO	SENCY AS	SISTANCE				
Product	Calcium Carl	bonate, Chips			CHEM		alth 0				
Chemical Synonyms	Marble Chips	-	800-42	24-9300 He	Emergency	and					
Formula	CaCO <sub>3</sub>			-   🔛	,	Re	First Aid Pr	ocedur	es		
Unit Size	up to 12 Kg.			- NFP	A RATING		anything by m with water for				
C.A.S. No.	471-34-1		SLIGHT MOI	DERATE SERIC	SKIN: Remove contaminated cl medical attention. INHALATION						
SECTIC	DN II	INGR	EDIENTS OF	MIXTURI	ES	-		difficult, give o			
Principal (	Component(	s)			%	TLV	Units	SECTION			
Calcium	Carbonate, Chi	ips			>99%	See	Section V.	- Stability $-$	Instable Stable	<b>)</b> ×	
								Incompatib			
CAUTIO	N! USE EXTR	EME CARE IN	THE USE OF MARE		I GENERA	ING CO.		(Materials to		d) <sup>V</sup>	
						2		Hazardous			
SECTIC	DN III	PHYS	SICAL DATA					Decomposi	tion Pro	oducts	
				es 826°C (1520°F) Specific Gravity				Hazardous Po		zation Not Occ	
Boiling Poir	Boiling Point (°F)			Percent Volatile by Volume (%)		N/A		May Occur	VVIII	X	
Vapor Pressure (mm Hg)		N/A		Evaporation Rate ( Butyl acetate		N/A		SECTION	VII		
Vapor Density (Air=1) N/A		N/A						Steps to be			
Solubility in	Water	0.001% @ 0°	C; 0.002% @ 100°C	).				material is r	elease	a or sp	
Appearance	e & Odor	White stone of	chips; no odor.								
SECTIC	N IV	FIRE	AND EXPLOS	SION HAZ	ZARD D			Waste Disp	osal Me	ethod	
Flash Point (Method Used	l) Non-fl	Non-flammable. Flammable Lii % by Volume				Lower	Upper				
Extinguisher Media		Use any media suitable for extinguishing supporting fire.  SECTION VIII Respiration Protection None sh									
SPECIAL I	FIREFIGHTIN		<b>r</b> 112					(Specify Type) Ventilation		work in Exhaust anical (Ge	
In fire conditions, wear a NIOSH/MSHA approved self-contained breathing apparatus and full protective								Protective 0	Bloves	1	
		c	lothing.					Other Protective Equipment		Goggles	
								SECTION			
	FIRE AND	;						Precautions to in Handling & Keep container tightly c	Storing		
			he fumes evolved b					Other Precaut	ions Re Fo	ead label on co or laboratory u	
	composed of calcium oxide (quick lime). This material is irritating to the skin, eyes, and mucous membranes.								Do	o not add ay result.	
								Revision No.	7 1	) ata	

Effects of	Overe	expo	LC tra ca	Low hazard as chips. Inhalation of respirable dusts may aggravate respiratory tracts. Exposure to dust may irritate skin and eyes. Ingestion should not cause any health problems. Exercise appropriate procedures to minimize potential hazards. Target rorgans: None known.								
Emergenc First Aid F			a – –		TION: Call physic of the contract of the contr						•	
with water f	or at lea nove cor ention. <u>I</u>	ist 15 ntamir INHAL	unconscious minutes, lift nated clothin <u>ATION:</u> Re	s pers ing up ng. Fli emove	on. <u>EYES:</u> Cho oper and lower e ush thoroughly e to fresh air. If	eck f eyelio with	or and rer Is occasio mild soap	nove con nally. Ge and wate	tact len et imme er. If irri	ses. Flush diate medio tation occu	thoroughly cal attention. rs, get	
SECTIO	N VI		R		TIVITY DA							
Stability	Unsta	Unstable		Conditions to Avoid								
ability	Stab	Stable						Acids.				
ncompati Materials		oid)	Will re	eact w	ith acids.							
lazardous Decompos		Proc	lucts	Reacts with acids to produce carbon dioxide.								
lazardous	Polym	eriza	tion	Con	nditions to A	٩vo	id					
May Occur	r ۱	Nill N	ot Occur					Not app	licable.			
			Х									
SECTIO	N VII		S	PILL	OR LEAK	( P	ROCEL	DURES	5			
Steps to b naterial is				d	Recover as place in a set taken to avo with soap as	uitab oid ca	le contain ausing due	er for pro	per disp	oosal. Care	e should be	
Vaste Dis	posal	Met	The	ese dis	e, treatment, or disp posal guidelines a of in accordanc	re inte	ended for th	e disposal	of catalo	g-size quanti	ities only.	
SECTIO	N VIII		S	PEC	IAL PROT	EC			ΜΔΤΙ	ON		
espiration Pr pecify Type)			lone should	be ne	eeded in normal on hood or wear	l labo	oratory ha	ndling. If	dusty c	onditions p	revail,	
entilation	n Lo	Local Exhaust		Recommended			Special			No.		
entilatio	Me	echani	cal (General)	Recommended		d	Other		No.			
rotective	Glove	es	Leath	ner or	rubber.	Ey	e Prote	ection	с	hemical sat	fety glasses.	
ther Protectiv quipment	/e	G	oggles, lab	coat,	proper gloves,	prop	er ventilat	ion if dus	ty.			
SECTIO	N IX		S	PEC	IAL PREC	AU	TIONS					
recautions h Handling				tore in	a dry place aw	ay fr	om acids.					
ep container tight	ly closed wh	en not in	use. W	ash th	horoughly after I	hand	lling.					
ther Preca	utions	Read For la	label on containe boratory use only	r before . Not for	using. Do not wear cor r drug, food or househol	ntact le Id use.	nses when wor Keep out of re	king with che	micals. en.			
					arble chips in a c and wash conta				erous ex	plosion		
evision N	0. 7	Па	te 01/01	/07	Approved		James A	Bertsch		nemical Safety	JAB	
						ould us						
he information cont nem and must make	tained hereir e independe	nt determ	shed without warrant	anty of a bility and	Approved iny kind. Employers sho completeness of inform Printed on recycled pag	nation f	James A. se this informati from all sources	ion only as a s	Co supplement	oordinator to other information	JAB ation gathered by and the safety and	

**HEALTH HAZARD DATA** 

Calcium carbonate, powder: TWA: 10 mg/m<sup>3</sup> ACGIH, 2001.

CC0060

NON-REGULATED.

D.O.T.